

JADEEKO

The **BRAND NEW 3C** (Compact, Competitive, Complete) Countertop and Mobile Payment Solution



TECHNICAL SPECIFICATIONS

| | | |
|------------------|---------------------|--|
| Processor | | RISC 32bit (ARM 7) |
| Memory | CyberAPI (Standard) | SDRAM: 8MB (Option: Up to 32MB) SRAM: 256KB/Battery back up (Option: Up to 512KB) Flash: 2MB (Option: Up to 4MB) |
| | Linux | SDRAM: 16MB (Option: Up to 32MB) SRAM: 256KB/Battery back up (Option: Up to 512KB) Flash: 2MB (Option: Up to 4MB) NAND: 16MB (Option: Up to 64MB) |
| Display | | 128 x 64 pixel graphic display Up to 8 lines x 21 characters, backlit |
| Keypad | | 19 keys |

| | | |
|--|-------------|--|
| Magnetic-stripe card reader | | Tracks: 1&2 or 2&3 Bi-directional |
| Smartcard reader | | ISO7816 compliant EMV level I (2000) certified |
| Security Access Module (SAM) | | 2 (Option: Up to 4) |
| Modem | | Async: 2400bps (Option: Up to 33.6Kbps) Sync: 1200, 2400bps |
| Peripheral ports (Optional) | Standard | RS232 x 2 Telco x 2 USB slave x 1 |
| | Ethernet | RS232 x 1 Telco x 2 LAN x 1 USB slave x 1 |
| | GSM GPRS | RS232 x 2 Telco x 2 USB slave x 1 |
| | WiFi | RS232 x 2 Telco x 2 USB slave x 1 |
| Printer | | 2" thermal 12 lines/sec Clamshell paper loading |
| Power | | Input: AC 100V ~ 240V, 50/60Hz Output: DC 8.0V/2.0A |
| Physical dimensions | | 110mm (W) x 248mm (L) x 91mm (H) |
| Weight | | 655g |
| Software environment (Optional) | | CyberAPI Linux |

CyberNet Inc
T +81.31.777.1830
F +81.31.777.1833
www.cybernetww.com